

*A ready-mixed, under-tile tanking system to protect water-sensitive substrates from exposure to water*

## webersys protect



### Uses

For protecting walls and floors that are sensitive to water in:

- Humid areas such as sanitary blocks, showers and kitchens
- Ideal for wet rooms prior to tiling

### Constraints

Not suitable for waterproofing exterior building walls, industrial floors or unstable surfaces.

Not suitable for tanking areas that are continually immersed, such as ponds and pools.

Not suitable for waterproofing roofs and terraces.

Not resistant to pressuring washing on some substrates.

### About this product

**webersys protect** is a ready-mixed, under-tile tanking system to protect water sensitive substrates from exposure to water.

### Technical data

#### Physical properties

|                              |                               |
|------------------------------|-------------------------------|
| Description                  | Blue aqueous paste            |
| Relative density             | 1.5                           |
| Coverage                     | Approx. 0.8 kg/m <sup>2</sup> |
| Drying time between coats    | 1½ – 2 hours at 20°C          |
| Drying time for fixing tiles | 3 – 4 hours at 20°C           |

#### Performance:

|                          |                        |
|--------------------------|------------------------|
| Initial adhesion         | ≥1.5 N/mm <sup>2</sup> |
| Adhesion after immersion | ≥1.2 N/mm <sup>2</sup> |
| Elongation at break      | 200%                   |
| Water permeability       | 0                      |

Note: these values were obtained under lab conditions and may be significantly different under site conditions.

### Features and benefits

- ▲ Protects water-sensitive substrates such as wood, plaster etc.
- ▲ Ready to use – no mixing required
- ▲ Easy to use – apply with a roller
- ▲ Supplied in shower-sized kit and trade pack

# webersys protect

## Preparation

Ensure that all surfaces are clean, completely dry, sound and free from dust grease or any other contaminating barrier. Any joints between wood panels must be fully supported to prevent movement.

Any existing covering must be sound and capable of supporting the expected load. Scrape off any flaking paint and replace any hollow sounding tiles. Emulsion paint is not suitable. Wash off any traces of maintenance products (wax etc.) or grease and allow to dry.

Prime porous surfaces, such as plaster or cement, with **weber PR360** and allow to dry for 2 hours.

Do not butt-joint or cut the tape short at corners. Overlap joints and all layers at corners bedding into **webersys protect**.

Generously apply the first coat of **webersys protect** to the area with a roller using around 0.4 kg/m<sup>2</sup>.

As soon as the first coat is dry, apply a second coat, rolling in a direction 90° to the first coat, to obtain an overall film around 1 mm thick. Wash tools in water immediately after use.

Allow to dry for at least 3 – 4 hours, or until the **webersys protect** is no longer tacky, before fixing the tiles with **weberset SPF** or **weberset rapid SPF**. When the adhesive has fully set, grout the joints with an appropriate grout. Fill the joints around the perimeters with **weberjoint silicone**.

## Health and safety

Essentially not hazardous.  
Not harmful during normal use.  
After contact with skin, wash immediately with plenty of water.  
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Keep out of the reach of children.

**For further information, please request the Material Safety Data Sheet for this product.**

## Application

**Do not apply if the temperature is outside of the range +5°C to +35°C and do not apply to frozen, thawing or hot substrates or in direct sunlight.**

Ensure that any concealed underfloor heating system is turned off and that the floor is cool.

Apply a coat of **webersys protect** with a flat brush to corners, angles, around protruding pipes, into small cracks (must be stable and less than 2 mm wide) and along the joints between wooden panels.

Place strips of **BE14** Joint Reinforcing Tape along the angles and cut to size with scissors so that all lengths fit tightly into any corners.

Reinforce around protruding pipes by cutting a star opening in a suitable length of tape, pushing the patch over the pipe and bedding it into the **webersys protect** tightly around the pipe.

Taking care not to damage the tape, work it into the **webersys protect** and smooth down with a flat trowel.

## Packaging

**webersys protect** is supplied in 7 kg plastic buckets or 1000 kg container.  
**BE14** joint reinforcing tape is supplied in 10 m rolls.

**webersys protect** is also available as a 5 kg kit comprising:  
1 kg **weber PR360**  
4 kg **webersys protect**  
7 m **BE14** tape

## Coverage

Up to 0.4 kg per coat per m<sup>2</sup>, depending on the porosity of the substrate.

## Storage and shelf life

When stored airtight in a cool, dry place at temperatures above 5°C and protected from frost, shelf life is 12 months from date of manufacture.

### Technical services

**Weber's** Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical helpline  
Tel: 08703 330 070  
e-mail [technical@netweber.co.uk](mailto:technical@netweber.co.uk)

### Sales enquiries

**Weber** products are distributed throughout the UK through selected stockists and distributors. Please contact the relevant Customer Services Team below for all product orders and enquiries.

UK and Ireland  
Tel: 08703 330 070  
Fax: 0800 014 2995  
e-mail [customerservice@netweber.co.uk](mailto:customerservice@netweber.co.uk)

### Saint-Gobain Weber

Dickens House, Enterprise Way, Maulden Road, Flitwick, Bedford MK45 5BY, UK  
Tel: 08703 330 070 Fax: 0800 014 2995 e-mail: [mail@netweber.co.uk](mailto:mail@netweber.co.uk)  
[www.netweber.co.uk](http://www.netweber.co.uk)

To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.